

Play value

A new level of exercise is created by simply stretching a line. Leaving the normally solid ground beneath you, suddenly poses completely new challenges. The continuous forward movement makes first mastering the capricious system a must. Playing companions or an accompanying person can offer a fixed point for the tightrope walker at the beginning to help them conquer the balancing act. The continuously evasive line pushes the user towards increasingly successful methods to triumph over the unsteadiness in free space. It quickly becomes clear that continuous balancing movements and control over the body's centre of gravity are the decisive skills needed to accomplish forward movement. Progressive exercises with backward movement, knee stands or an inclined line remain an option for the practised user.



Fundamental characteristics

- intensification of standard balancing offers
- promotes complex physical control
- exercise activity: equilibrium, body tension, balance



Suitable


- for children from 6 years of age
- leisure areas
- parks
- open-air swimming pools

Slackline


Notes

In unsupervised public areas, it may be the operator's duty to maintain safety. Please pay attention to local regulations. If the slackline system is installed permanently, we recommend the following maintenance measures:

- inspecting the slackline on a regular basis (at least once a week)
- installing a multilingual information board with instructions for proper use of the system (1 person at a time, max. weight 150 kg, no manipulation of the system, phone number for reporting damage, etc.)
- legal disclaimer for cases of improper use
- securing the ratchet with a padlock



7.15500



Technical information

de-barked posts
de-barked stand posts, Ø approx. 25 cm, of robinia



angle cut

vertical stand posts with angle cut in the end grain section as constructive wood preservation



textile belt, standard colour blue

Dimensions

(small deviations possible)

distance between posts up to 10 m possible

belt strap width 50 mm

weight 200 kg

safety check according to EN 1176

Components

- 2 stand posts
- 1 belt incl. fastening material capacity up to 150 kg
- 1 padlock as safety device for the ratchet

Installation information

Surfacing requirements corresponding to a fall height of ≤ 1.00 m (please refer to price list for more detailed information)

Recommendation: lawn, sand, gravel or wood chips

Foundations


2 items 100 x 100 x 100 cm excavation depth 120 cm

Attention:

Exact measurements may vary; for all installation dimensions refer to current assembly instructions.

Technical changes reserved.

Equipment also available with steel posts.



7.15500